

VCL

Refrigerant condensers











Key benefits

- Low height
- Easy installation
- Quiet

VCL characteristics

- Counter flow, centrifugal fan, forced draft
- PED 2014/68/EU coil design

Capacity range

180 - 1340 kW (for single cell models, nominal R22 kW's)

Typical applications

- Low height requirements
- Tight enclosures and installations requiring a single air inlet
- Indoor installations
- Sound critical installations
- Dry operation in winter time



Low height

• Very low height: fits perfectly on roof tops or tight enclosures.

Easy installation

- VCL condensers are factory-assembled. We ship in one piece for easy on-site lifting and installation.
- VCL offers high capacity and minimum operating weight. **Save on steel supports**, both underneath the equipment and in the building itself for rooftop installations.
- Single-side air inlet lets you install **next to solid walls**.
- Units housable **indoors** thanks to centrifugal fans allowing intake or discharge ductwork.

Ideal for a quiet operation

- VCL units include quiet internal centrifugal fans for minimal surrounding noise.
- Single-side air inlet, and a quieter condenser rear for more noise-sensitive areas.
- Cut operation noise still further with factory-designed and tested **sound attenuators** or silencers.

Year-round reliable operation

- Various corrosion-resistant materials, including the unique <u>Baltibond hybrid coating</u> for guaranteed long service life.
- Optional Baltiguard Drive System for energy savings and less noise during low load (night). A perfect stand-by system in case of motor failure
- Optional extended surface coil with steel fins for dry operation.

Interested in the VCL evaporative condenser for your industrial refrigeration application? Contact your local <u>BAC representative</u> for more information.

Downloads

- VCL evaporative condenser
- BAC condenser overview
- Operating and Maintenance VCL
- Rigging and Installation VCL
- Spare Parts for VCL
- Retrofit Opportunities for VCL