



# DCV-AD

Previous generation products



## Key benefits

- High thermal performance
- Saving water
- Top hygiene control

### DCV-AD, TrilliumSeries characteristics

Counter flow, adiabatic pre-cooling, axial fan, induced draft

### Capacity range

340 - 1030 kW

### Typical applications

- Small to medium industrial refrigeration applications
- Locations with limited water and space availability



## Boosting high thermal performance

- **Pads** in front of the finned coil pre-cool air to virtual **wet bulb temperature**.
- Up to **40% improved capacity** compared to dry cooling.
- DCV-AD condenser consumes **less energy**.
- DCV-AD condenser achieves **low process temperatures**.

## Saving water

- TrilliumSeries condensers **achieve annual water savings exceeding 80%** water compared to normal water cooled condensers by limited adiabatic operation.

## Top hygiene control

- Featuring a **once-through system**: recirculation and stagnation of water eliminated.
- **No stagnant water**: pre-cooler water conveyed from pads to sewer via a gutter.
- **No aerosol formation**: TrilliumSeries condensers minimize the Legionella risk.
- TrilliumSeries condensers cool incoming air **without transferring water** to the dry coil

Interested in the TrilliumSeries condenser for your refrigeration project? Contact your local [BAC representative](#) for more information.

## Downloads

- [DCV-AD condenser](#)
- [Operating and Maintenance DCV-AD](#)